

PRODUCT INFORMATION

Hahn & Sohn HDE350RST3 diesel generator
ComAp remote management (optional accessory)

Rated Power: 350 kVA / 280 kW Output Voltage: 230 V / 400 V Fuel Consumption at 50% Load: 37 l/h Weight (net): 4,010 kg



PARAMETER	VALUE
Category	Industrial power generators
Warranty	2 years
Weight	4010 kg
Maximum power	385 kVA / 308 kW
Rated power	350 kVA / 280 kW
Rated current	505 A
Frequency	50 Hz
Nominal voltage	230 V / 400 V
Fuel tank capacity	490 l
Operating time on a full tank at 100% load	6.7 hours

PARAMETER	VALUE
Fuel consumption at 100% load	72.9 l/h
Fuel consumption at 75% load	54.1 l/h
Fuel consumption at 50% load	37 l/h
Dimensions	4200 x 1500 x 2200 mm
Engine type	Diesel
Engine power	307 kW
Engine speed	1500 rpm
Number and arrangement of cylinders	6 / in line
Engine fuel system	direct injection
Exhaust gas flow	41.5 m ³ /min
Exhaust gas temperature	600 °C
Voltage regulation	electronic - AVR
Voltage stability	± 1%
Oil tank capacity	36 l

Data from Hahn & Sohn product documentation. Before selecting a model, confirm the intended application, configuration and operating conditions.

Full information: <https://hahn-sohn-eu.vercel.app/en/hahn-sohn-naftova-elektrocentrala-hde350rst3/>