

PRODUCT INFORMATION

Hahn & Sohn Diesel Generator HDE80SS3 ComAp remote management (optional accessory)

Rated Power: 75 kVA / 60 kW Output Voltage: 230 V / 400 V Fuel Consumption at 50% Load: 12.59 l/h Weight (net): 1,440 kg



PARAMETER	VALUE
Category	Industrial power generators
Warranty	2 years
Weight	1440 kg
Fuel tank capacity of the generator	164 l
Starter	Electric
Voltage	230/400 V
Maximum power (400V/230V)	82.5 kVA / 66 kW
Rated power (400V/230V)	75 kVA / 60 kW
Frequency, Hz	50
Voltage regulation	AVR

PARAMETER	VALUE
Rated current, A	108.7
Engine type	four-cylinder, direct injection, water-cooled
Engine power, kW	75
Displacement, cm ³	4300
Dimensions, mm	2350 x 970 x 1350
Noise level, dB	53
Number of revolutions, min	1500
Operating time on a full tank at 100% load, h	7.8
Fuel consumption at 100% load, l/h	20.94
Fuel consumption at 75% load, l/h	16.27
Fuel consumption at 50% load, l/h	12.59
Oil tank capacity, l	17
Coolant tank capacity, l	25.9
Coolant type	Antifreeze -38 °C

Data from Hahn & Sohn product documentation. Before selecting a model, confirm the intended application, configuration and operating conditions.

Full information: <https://hahn-sohn-eu.vercel.app/en/hahn-sohn-dieselovy-generator-hde80ss3/>