

PRODUCT INFORMATION

Hahn & Sohn HDE60RST3-5 diesel generator
ComAp remote management (optional accessory)

Rated Power: 60 kVA / 48 kW Output Voltage: 230 V / 400 V Fuel Consumption at 50% Load: 7 l/h Weight (net): 1,170 kg



PARAMETER	VALUE
Category	Industrial power generators
Warranty	2 years
Weight	1170 kg
Maximum power	66 kVA / 55 kW
Rated power	60 kVA / 48 kW
Rated current	87 A
Frequency	50 Hz
Nominal voltage	230 V / 400 V
Fuel tank capacity	120 l
Operating time on a full tank at 100% load	8.5 hours

PARAMETER	VALUE
Fuel consumption at 100% load	14 l/h
Fuel consumption at 75% load	10.6 l/h
Fuel consumption at 50% load	7 l/h
Dimensions	2320 x 990 x 1290 mm
Engine type	diesel, four-cylinder, turbo, direct injection, water-cooled
Displacement	4210 cm ³
Engine power	255 kW
Engine speed	1500 rpm
Number and arrangement of cylinders	4 / in line
Engine power system	direct injection, turbo
Voltage regulation	electronic - AVR
Voltage stability	± 1%
Oil tank capacity	14 l
Coolant tank capacity	28 l
Coolant type	Antifreeze -38 °C
Battery weight	20 kg

Data from Hahn & Sohn product documentation. Before selecting a model, confirm the intended application, configuration and operating conditions.

Full information: <https://hahn-sohn-eu.vercel.app/en/hahn-sohn-naftova-elektrocentrala-hde60rst3-5/>