

PRODUCT INFORMATION

Hahn & Sohn HDE313RSP3-3 diesel generator

Rated Power: 250 kW / 313 kVA Output Voltage: 230 V / 400 V Fuel Consumption at 50% Load: ~33.8 l/h Weight (net): 3450 kg



| PARAMETER           | VALUE                                      |
|---------------------|--------------------------------------------|
| Category            | Industrial power generators                |
| Warranty            | 2 years                                    |
| Weight              | 3450 kg                                    |
| Prime Power (PRP)   | 313 kVA / 250 kW                           |
| Standby Power (LTP) | 344 kVA / 275 kW                           |
| Rated current       | 452 A                                      |
| Voltage             | 400/230 V                                  |
| Frequency           | 50 Hz                                      |
| Power factor        | cos φ 0,8                                  |
| Model               | PEZAL PPA313-250V                          |
| Type                | Soundproofed on frame with integrated tank |

| PARAMETER                       | VALUE                 |
|---------------------------------|-----------------------|
| Emissions                       | EU Stage 3A           |
| Volume                          | 11,8 l                |
| Rotation speed                  | 1500 rpm              |
| PRP engine power                | 307 kW                |
| Fuel                            | Diesel (EN590)        |
| Consumption at 100% load        | ~66,9 l/h             |
| Consumption at 75% load         | ~49,0 l/h             |
| Consumption at 50% load         | ~33,8 l/h             |
| Oil filling                     | 41 l                  |
| Coolant                         | 23,2 l                |
| Number of poles                 | 4                     |
| Connection                      | Star                  |
| Insulation class                | H                     |
| Coverage                        | IP23                  |
| Voltage regulation              | AVR                   |
| Voltage stability               | ±1 %                  |
| THD                             | < 2,5 %               |
| Effectiveness                   | 94,5 %                |
| Tank capacity                   | 750 l                 |
| Operation on a full tank (100%) | approx. 11 mth        |
| Dimensions (L × W × H)          | 4050 × 1400 × 2150 mm |

Data from Hahn & Sohn product documentation. Before selecting a model, confirm the intended application, configuration and operating conditions.

Full information: <https://hahn-sohn-eu.vercel.app/en/hahn-sohn-naftova-elektrocentrala-hde313rsp3-3/>