

PRODUCT INFORMATION

Hahn & Sohn HDE200RST3-3 diesel generator
ComAp remote management (optional accessory)

Rated Power: 200 kVA / 160 kW Output Voltage: 230 V / 400 V Fuel Consumption at 50% Load: 20.6 l/h Weight (net): 2,621 kg



PARAMETER	VALUE
Category	Industrial power generators
Warranty	2 years
Weight	2621 kg
Maximum power	220 kVA / 176 kW
Rated power	200 kVA / 160 kW
Rated current	289 A
Frequency	50 Hz
Nominal voltage	230 V / 400 V
Fuel tank capacity	350 l
Operating time on a full tank at 100% load	8.5 hours

PARAMETER	VALUE
Fuel consumption at 100% load	41 l/h
Fuel consumption at 75% load	31 l/h
Fuel consumption at 50% load	20.6 l/h
Dimensions	3130 x 1120 x 1800 mm
Engine type	Diesel, four-cylinder, direct injection, water-cooled
Engine power	180 kW
Engine speed	1500 rpm
Number and arrangement of cylinders	4 / in line
Engine fuel system	direct injection
Exhaust gas temperature	600 °C
Voltage regulation	electronic - AVR
Voltage stability	± 1%
Oil tank capacity	15-17.5 l

Data from Hahn & Sohn product documentation. Before selecting a model, confirm the intended application, configuration and operating conditions.

Full information: <https://hahn-sohn-eu.vercel.app/en/hahn-sohn-naftova-elektrocentrala-hde200rst3-3/>