PRODUCT INFORMATION

Hahn & Sohn HDE670RST3 diesel generator ComAp remote management (optional accessory)

Rated Power: 670 kVA / 536 kW Output Voltage: 230 V / 400 V Fuel Consumption at 50% Load: 72 l/h Weight (net): 6,500 kg

PARAMETER	VALUE
Category	Industrial power generators
Warranty	2 years
Weight	6500 kg
Maximum power	737 kVA / 590 kW
Rated power	670 kVA / 536 kW
Rated current	967 A
Frequency	50 Hz
Nominal voltage	230 V / 400 V
Fuel tank capacity	1300 l
Operating time on a full tank at 100% load	9 hours

PARAMETER	VALUE
Fuel consumption at 100% load	143.9 l/h
Fuel consumption at 75% load	107.9 l/h
Fuel consumption at 50% load	72 l/h
Dimensions	4900 x 2100 x 2400 mm
Engine type	Diesel
Engine power	602 kW
Engine speed	1500 rpm
Number and arrangement of cylinders	12 / in line
Engine fuel system	direct injection
Exhaust gas flow	138 m³/min
Exhaust gas temperature	650 °C
Voltage regulation	electronic - AVR
Voltage stability	± 1%
Oil tank capacity	45 l

Data from Hahn & Sohn product documentation. Before selecting a model, confirm the intended application, configuration and operating conditions.

Full information: https://hahn-sohn-eu.vercel.app/en/hahn-sohn-naftova-elektrocentrala-hde670rst3/