PRODUCT INFORMATION

Hahn & Sohn HDE120RST3-3 diesel generator ComAp remote management (optional accessory)

Rated Power: 120 kVA / 96 kW Output Voltage: 230 V / 400 V Fuel Consumption at 50% Load: 13.2 l/h Weight (net): 2,000 kg

PARAMETER	VALUE
Category	Industrial power generators
Warranty	2 years
Weight	2000 kg
Maximum power	132 kVA / 106 kW
Rated power	120 kVA / 96 kW
Rated current	173 A
Frequency	50 Hz
Nominal voltage	230 V / 400 V
Fuel tank capacity	265 l
Operating time on a full tank at 100% load	10 hours

PARAMETER	VALUE
Fuel consumption at 100% load	26.4 l/h
Fuel consumption at 75% load	19.8 l/h
Fuel consumption at 50% load	13.2 l/h
Dimensions	2160 x 1050 x 1530 mm
Engine type	Diesel, four-cylinder, direct injection, water-cooled
Engine power	120 kW
Engine speed	1500 rpm
Number and arrangement of cylinders	4 / in line
Engine fuel system	direct injection
Exhaust gas temperature	600 °C
Voltage regulation	electronic - AVR
Voltage stability	± 1%
Oil tank capacity	13 l

Data from Hahn & Sohn product documentation. Before selecting a model, confirm the intended application, configuration and operating conditions.

Full information: https://hahn-sohn-eu.vercel.app/en/hahn-sohn-naftova-elektrocentrala-hde120rst3-3/