PRODUCT INFORMATION

Hahn & Sohn Diesel Generator HDE40SS3 ComAp remote management (optional accessory)

Rated Power: 37 kVA / 30 kW Output Voltage: 230 V / 400 V Fuel Consumption at 50% Load: 5.58 l/h Weight (net): 1,060 kg

PARAMETER	VALUE
Category	Industrial power generators
Warranty	2 years
Weight	1060 kg
Fuel tank capacity of the generator	120 l
Starter	Electric
Voltage	230/400 V
Maximum power (400V/230V)	41 kVA / 33 kW
Rated power (400V/230V)	37 kVA / 30 kW
Frequency, Hz	50
Voltage regulation	AVR

PARAMETER	VALUE
Rated current, A	54.1
Engine type	four-cylinder, direct injection, water-cooled
Motor power, kW	38
Displacement, cm³	4087
Dimensions, mm	1950 x 950 x 1200
Noise level, dB	51
Number of revolutions, min	1500
Operating time on a full tank at 100% load, h	13.5
Fuel consumption at 100% load, l/h	8.8
Fuel consumption at 75% load, l/h	6.75
Fuel consumption at 50% load, l/h	5.58
Oil tank capacity, l	13
Coolant tank capacity, l	18.4
Coolant type	Antifreeze -38 °C
Battery weight, kg	11.5 kg

Data from Hahn & Sohn product documentation. Before selecting a model, confirm the intended application, configuration and operating conditions.

Full information: https://hahn-sohn-eu.vercel.app/en/hahn-sohn-dieselovy-generator-hde40ss3/