PRODUCT INFORMATION

Hahn & Sohn HDE60RST3 diesel generator ComAp remote management (optional accessory)

Rated Power: 60 kVA / 48 kW Output Voltage: 230 V / 400 V Fuel Consumption at 50% Load: 8.2 l/h Weight (net): 1,150 kg

PARAMETER	VALUE
Category	Industrial power generators
Warranty	2 years
Weight	1150 kg
Maximum power	66 kVA / 53 kW
Rated power	60 kVA / 48 kW
Rated current	87 A
Frequency	50 Hz
Nominal voltage	230 V / 400 V
Fuel tank capacity	120 l
Operating time on a full tank at 100% load	8.2 hours

PARAMETER	VALUE
Fuel consumption at 100% load	15.6 l/h
Fuel consumption at 75% load	11.8 l/h
Fuel consumption at 50% load	8.2 l/h
Dimensions	2320 x 990 x 1290 mm
Noise level	97 dB(A)
Engine type	diesel, four-cylinder, direct injection, water-cooled
Engine power	63 kW
Displacement	4100 cm3
Engine speed	1500 rpm
Number and arrangement of cylinders	4 / in line
Engine fuel system	direct injection
Voltage regulation	electronic - AVR
Voltage stability	± 1%
Oil tank capacity	12.5 l
Coolant tank capacity	15 l
Coolant type	Antifreeze -38 °C
Battery weight	20 kg

Data from Hahn & Sohn product documentation. Before selecting a model, confirm the intended application, configuration and operating conditions.

Full information: https://hahn-sohn-eu.vercel.app/en/hahn-sohn-naftova-elektrocentrala-hde60rst3/