

PRODUCT INFORMATION

Hahn & Sohn HDE250RST3-3 diesel generator
ComAp remote management (optional accessory)

Rated Power: 250 kVA / 200 kW Output Voltage: 230 V / 400 V Fuel Consumption at 50% Load: 26.9 l/h Weight (net): 2,500 kg



PARAMETER	VALUE
Category	Industrial power generators
Warranty	2 years
Weight	2500 kg
Maximum power	275 kVA / 220 kW
Rated power	250 kVA / 200 kW
Rated current	361 A
Frequency	50 Hz
Nominal voltage	230 V / 400 V
Fuel tank capacity	530 l
Operating time on a full tank at 100% load	10.3 hours

PARAMETER	VALUE
Fuel consumption at 100% load	53.6 l/h
Fuel consumption at 75% load	40 l/h
Fuel consumption at 50% load	26.9 l/h
Dimensions	2790 x 1250 x 1850 mm
Engine type	Diesel, direct injection, water-cooled
Engine power	228 kW
Engine speed	1500 rpm
Number and arrangement of cylinders	6 / in line
Engine fuel system	direct injection
Exhaust gas flow	41 m³/min
Exhaust gas temperature	600 °C
Voltage regulation	electronic - AVR
Voltage stability	± 1%
Oil tank capacity	25 l

Data from Hahn & Sohn product documentation. Before selecting a model, confirm the intended application, configuration and operating conditions.

Full information: <https://hahn-sohn-eu.vercel.app/en/hahn-sohn-naftova-elektrocentrala-hde250rst3-3/>